

electronic board
UB-5315 UB-5815 UB-5310

Panaboard™



General	Model number	UB-5315	UB-5815	UB-5310
Power Supply		AC 100 - 120 V, 50/60 Hz or AC 220 - 240 V, 50/60 Hz		
Power Consumption (Operational)		1.40 A (AC 100 - 120 V) 0.75 A (AC 220 - 240 V)		
External dimensions (Height X Width X Depth, without stand)		1,334 mm X 1,372 mm X 212 mm	1,334 mm X 1,735 mm X 212 mm	1,440 mm x 1,372 mm x 233 mm
Weight (without stand)		25 kg (55.1 lbs)	27 kg (59.5 lbs)	23 kg (50.7 lbs)
Ambient operating conditions		Temperature: 10-35 °C (50-95 °F) Humidity: 30-80% RH		
Writing implements		Dry erase felt-tipped markers (black, red and blue)		
Input Block				
Panel dimensions (Height X Width)		900 mm X 1,275 mm	900 mm X 1,638 mm	900 mm X 1,275 mm
Panel surface		2		
Panel advance system		Endless scroll type		
Copying area (Height X Width)		850 mm X 1,250 mm	850 mm X 1,613 mm	850 mm X 1,250 mm
Scanning system		Image sensor		
Output Block				
Printing		Fusion thermal transfer type		Thermal type
Copy paper		Standard or recycled paper		Heat-sensitive roll paper Paper thickness : 65 µm Core diameter : 25.4 mm or more
Copy paper size		A4/Letter*		
Copy density		8 dots/mm		
Copy color		Black		
Contrast adjustment		Two levels : Normal/Dark		
2-screen compressed copying		Yes		
Time required for Copying		15 s/sheet		
Continuous copies		1 to 9		
Paper empty indication		Yes		
Automatic cutter		—		Yes
Computer Interfacing System Requirements				
Computer		IBM® PC/AT or compatible machine with a CD-ROM drive		
CPU		Pentium® II or higher processor		
Interface		USB 1.1 (B connector)		
OS		Windows® 98/Me/2000/XP		
Memory		64 MB or more (Windows® 98/Me) 128 MB or more (Windows® 2000) 256 MB or more (Windows® XP)		
HD		At least 40 MB free space (except saving space for image file)		
Accessories				
<ul style="list-style-type: none"> • Markers (Black, Red, Blue) • Eraser • Software CD-ROM • Operating instructions, Installation manual • Wall-mount kit (Upper, Lower) • Thermal transfer film (for UB-5315, UB-5815) • Thermal paper roll (for UB-5310) 				
Separately Available				
Stand : UE-608005				
Replacement film : UG-6001 (Set of 2 rolls [50m] for UB-5315, UB-5815)				
Markers : KX-B031 (set of 10 black markers), KX-B032 (set of 10 red markers), KX-B033 (set of 10 blue markers)				
Erasers : KX-B042 (set of 6 erasers)				
Marker and eraser set : KX-B035 (contains 1 black, 1 red, and 1 blue markers and 1 eraser)				

* Letter size is for U.S.A. and Canada models.

Note:
 • Microsoft and Windows are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.
 • Windows® is Microsoft® Windows® operating system.
 • IBM is a registered trademark of International Business Machines Corporation.
 • Pentium is a registered trademark of Intel Corporation in the U.S. and other countries.
 • All trademarks referred to in this catalog are property of their respective companies.

<http://panasonic.co.jp/pcc/en/>
<http://www.panasonic.co.jp/global>

Design and specifications are subject to change without notice. KME0203/EU-5315ULC-01 Printed in Japan



Panasonic®



Microsoft®
 Windows® 98,
 Windows® Me,
 Windows® 2000,
 Windows® XP
 operating systems
 USB 1.1

**Panaboard takes notes instead of you
 Improves your Presentations and meetings**

